



1N4148

DIODE

HIGH-SPEED SWITCHING DIODE



DESCRIPTION

The UTC **1N4148** is designed for high-speed switching application in hybrid thick-and thin-film circuits. The devices is manufactured by the silicon epitaxial planar process and packed in plastic surface mount package.

FEATURES

- * Ultra-high speed
- * Low forward voltage
- * Fast reverse recovery time


SYMBOL







ORDERING INFORMATION

| Ordering Number | | Package | Pin Assignment | | | Packing |
|-----------------|---------------|---------|----------------|----|---|-----------|
| Lead Free | Halogen Free | | 1 | 2 | 3 | |
| 1N4148L-AE3-R | 1N4148G-AE3-R | SOT-23 | A | NC | C | Tape Reel |
| 1N4148L-AL3-R | 1N4148G-AL3-R | SOT-323 | A | NC | C | Tape Reel |
| 1N4148L-CA2-R | 1N4148G-CA2-R | SOD-123 | A | C | - | Tape Reel |
| 1N4148L-CB2-R | 1N4148G-CB2-R | SOD-323 | A | C | - | Tape Reel |
| 1N4148L-CC2-R | 1N4148G-CC2-R | SOD-523 | A | C | - | Tape Reel |

Note: Pin assignment: A: Anode C: Cathode NC: No Connection

| | |
|--|---|
| <p>1N4148G-AE3-R</p>  | <p>(1) R: Tape Reel (2) AE3: SOT-23, AL3: SOT-323, CA2: SOD-123, CB2: SOD-323, CC2: SOD-523 (3) G: Halogen Free and Lead Free, L: Lead Free</p> |
|--|---|

■ MARKING

| SOT-23 / SOT-323 | SOD-123 |
|--|---|
|  S8 → L: Lead Free G: Halogen Free |  S8 → L: Lead Free G: Halogen Free |
| SOD-323 | SOD-523 |
|  4148 → L: Lead Free G: Halogen Free |  S8 → L: Lead Free G: Halogen Free |

■ **ABSOLUTE MAXIMUM RATINGS** ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

| PARAMETER | | SYMBOL | RATINGS | UNIT |
|---|-----------------------|-------------|------------|--------------------|
| Maximum Repetitive Reverse Voltage | | V_{RRM} | 100 | V |
| Average Rectified Forward Current | | $I_{F(AV)}$ | 200 | mA |
| Non-repetitive Peak Forward Surge Current | Pulse Width = 1.0 sec | I_{FSM} | 1.0 | A |
| | Pulse Width = 1.0 ms | | 4.0 | A |
| Power Dissipation(Note 3) | SOT-23 | P_D | 350 | mW |
| | SOD-123 | | 400 | |
| | SOT-323 | | 270 | |
| | SOD-323/SOD-523 | | 200 | |
| Junction Temperature | | T_J | +175 | $^{\circ}\text{C}$ |
| Storage Temperature | | T_{STG} | -65 ~ +200 | $^{\circ}\text{C}$ |

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. These ratings are based on a maximum junction temperature of 200°C .

3. Device mounted on FR-4 PCB minimum land pad.

■ **THERMAL DATA**


| CHARACTERISTIC | | SYMBOL | RATINGS | UNIT |
|---------------------|-----------------|---------------|---------|-----------------------------|
| Junction to Ambient | SOT-23 | θ_{JA} | 357 | $^{\circ}\text{C}/\text{W}$ |
| | SOD-123 | | 312 | |
| | SOT-323 | | 460 | |
| | SOD-323/SOD-523 | | 500 | |

■ **ELECTRICAL CHARACTERISTICS** ($T_A=25^{\circ}\text{C}$, unless otherwise specified)


| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|-----------------------|----------|--|-----|-----|-----|---------------|
| Breakdown Voltage | V_R | $I_R = 100\mu\text{A}$ | 100 | | | V |
| | | $I_R = 5.0\mu\text{A}$ | 75 | | | V |
| Forward Voltage | V_F | $I_F = 10\text{ mA}$ | | | 1.0 | V |
| Reverse Current | I_R | $V_R = 20\text{ V}$ | | | 25 | nA |
| | | $V_R = 75\text{ V}$ | | | 5.0 | μA |
| Total Capacitance | C_T | $V_R = 0, f = 1.0\text{MHz}$ | | | 4.0 | pF |
| Reverse Recovery Time | t_{rr} | $I_F = 10\text{ mA}, V_R = 6.0\text{ V (60mA)}$ $I_{RR} = 1.0\text{ mA}, R_L = 100\Omega$ | | | 4.0 | ns |

TYPICAL CHARACTERISTICS


Reverse Voltage vs. Reverse Current
BV - 1.0 ~ 100 μ A




Reverse Current vs. Reverse Voltage
IR - 10 ~ 100 nA




Forward Voltage vs. Forward Current
VF - 1 ~ 100 μ A




Forward Voltage vs. Forward Current
VF - 0.1 ~ 10 mA






Forward Voltage vs. Forward Current
VF - 10 ~ 800 mA



Forward Voltage vs. Ambient Temperature
VF - 0.01 - 20 mA (-40 ~ +65°C)



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.